



TMB-251-LT

Communication card for addressable control panels CAD-150 series with network topology S-Network

Description

The communication card TMB-251-LT has different output ports for the following functions:

- 1 x RS-485 for the addressable control panels network (S-Network) (1)
- 1 x Ethernet for connection:
 - Detnov Cloud application
 - Remote Center application(SGD-RCD)
 - Integrations with third parties through the Modbus IP protocol

The network of addressable control panels and repeaters can be ring or bus, with a maximum of 32 nodes.

Maximum distance between two nodes:

TMB-251-LT: 1 km (Copper)

It incorporates an electrical isolation circuit between nodes, which allows to amplify the transmission of the network signal, being able to reach long distances in the first node of the network and the last one.

For example, if we had a network of 5 nodes, the maximum total distance of the network would be 5 km.

The TMB-251-LT network card adds the Modbus IP functionality to the addressable control panels CAD-150 series, allowing remote control of the main functions of these devices.

It allows the remote control and visualization of the fire detection installations through the Detnov Cloud application,SGD-RCD(Remote Center).

Compatible with graphic software SGD-151.

(1) S-Network only supports cards of model TMB-251 and TMB-251-LT

Technical features

S-Network topology features	
Maximum nodes in the network:	32
Maximum distance between nodes:	1 Km
Maximum network coverage:	32 Km
Operating mode:	Peer to peer
Connections	
2 x 1,5 mm ² twisted and shielded cable ⁽²⁾	
Environment	
Operating temperature:	From -5°C to +40°C
Relative humidity:	95% without condensation

(2) Use the "System Calculator" tool to check the maximum number of devices and loop length, in accordance with the cross-section of the cable used.